

	SK-1000A	SK-1000B
Measurement Range	Sphere	-25.00 ~ +25.00D (0.01/0.06/0.12/0.25D)
	Cylinder Degree	0.00 ~ ±10.00D (0.01/0.06/0.12/0.25D)
	Cylinder Axis	0°~180° (1°)
	Addition Degree	0.00 ~ +10.00D (0.01/0.06/0.12/0.25D)
	Prism Degree	0.00△ ~15.00△ (0.01/0.06/0.12/0.25D)
Measurable Lens	single/double optical lens	
	progressive multifocal lens	
	sunglasses (for transmittance measurement)	
Measurement of Prism	polar coordinates (△, °) , rectangular coordinates	
Measurement of PD	20.0mm to 48.0mm (monocular PD) , PD of single lens	
Transmittance of UV	support	support
Transmittance of Blue Light	support	support
Transmittance of Visible Light	/	support
Printer	thermal printer	
	manual paper cutting	automatic paper cutting
	printing paper 58mm×25mm	
Power Supply	main engine: DC 5V	
	power adapter: input AC 110V-240V, 50Hz-60Hz	
Power	30VA	
Size	255mm×210mm×430mm	
Weight	about 5kg	

TECNOIMAGEN

www.tecnoimagen.com.ar | 11-4582-2222

MULTI FUNCTIONAL AUTO LENSMETER

REDEFINING
FULL
FUNCTIONALITY
EASIER
TO
OPERATE



**AUTO
LENSMETER**
SK-1000A/B



AUTO LENSMETER
SK-1000A/B

Accuracy
Easy
Comfortable

“
Pursue for
the Ultimate of
Convenience
and Precision

Exquisite Design

Only weighs 5kg, soft curved body and classic ivory

Touch Screen

7-inch HD LCD screen for more delicate display

Comfortable touch screen design for smooth operation



Quick

More efficient image-

processing ability

Higher operation speed more

than 15 frames / MS

Fluent

More smooth cursor follow

Linear linkage with monitor

Great measurement accuracy

and speed

• Automatic identification on lens

In automatic measurement mode, the mode can be automatically switched based on specific types of lens

• Measurement of PD and PH

Moving nose slider and with sensor, PD and PH can be automatically generated, which is more convenient and faster

• Measurement of transmittance

the transmittance of blue light, visible light and UV can be measured at the same time, sunglasses with quantitative color intensity can be recommended

